

CAS Number: 27138-31-4, 120-55-

3

Product Description: Thamesflex

705

SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

CAS Number: 27138-31-4, 120-55-8

Product Name: Thamesflex 705

Revision Date: Jan 27, 2023 Date Printed: Jan 27, 2023

Version: 1.0 Supersedes Date: N.A.

Manufacturer's Name: Thames River Chemical Corp.

Address: 5230 Harvester Road Burlington, ON, CA, L7L 4X4

Emergency Phone: CHEMTREC (800) 424-9300

Information Phone Number: 905-681-5353

Fax: 905-681-5377

Product/Recommended Uses: For laboratory or industrial use only.

SECTION 2) HAZARDS IDENTIFICATION

Classification

Acute toxicity Dermal - Category 5

Acute toxicity Oral - Category 5

Acute aquatic toxicity - Category 3

Chronic aquatic toxicity - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms

None

Signal Word

Warning

Hazardous Statements - Health

H313 - May be harmful in contact with skin

H303 - May be harmful if swallowed

Hazardous Statements - Environmental

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P273 - Avoid release to the environment.

Precautionary Statements - Response

P312 - Call a POISON CENTER or doctor, if you feel unwell.

Precautionary Statements - Storage

No precautionary statement available.

Thamesflex 705 Page 1 of 7



CAS Number: 27138-31-4, 120-55-

3

Product Description: Thamesflex

705

Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local/national/international regulation. Waste management should be in full compliance with national, regional and local laws.

CAS Chemical Name % By Weight 0027138-31-4 PROPANOL, OXYBIS-, DIBENZOATE 65-85% 0000120-55-8 DIETHYLENE GLYCOL DIBENZOATE 10-30%

SECTION 4) FIRST-AID MEASURES

Inhalation

Get medical advice/attention if you feel unwell or are concerned. Remove source of exposure or move person to fresh air and keep comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor.

Eye Contact

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

Skin Contact

If skin irritation occurs or you feel unwell: Get medical advice/attention. Rinse with lukewarm, gently flowing water for 5 minutes or until product is removed. Call a POISON CENTER or doctor, if you feel unwell. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes or until medical aid is available. Wash contaminated clothing before reuse.

Ingestion

Rinse mouth. If you feel unwell/If concerned: Get medical advice/attention.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire: Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards in Case of Fire

Fire will produce irritating gases. Runoff may pollute waterways

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Thamesflex 705 Page 2 of 7



CAS Number: 27138-31-4, 120-55-

3

Product Description: Thamesflex

705

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Isolate hazard area and keep unauthorized personnel away. Stay uphill and/or upstream. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Recommended Equipment

Wear chemical protective clothing.

Personal Precautions

Avoid breathing vapor or mist. Avoid contact with skin, eye or clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal. Ventilate area after clean-up is complete.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Avoid contact with skin, eye or clothing. Avoid breathing vapor or mist. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. All containers must be properly labelled. Eyewash stations and showers should be available in areas where this material is used and stored

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Store in a cool, dry, well ventilated area, away from sources of ignition and incompatibilities. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Thamesflex 705 Page 3 of 7



CAS Number: 27138-31-4, 120-55-

Product Description: Thamesflex

705

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

None of the chemicals in Section 3 are regulated under "ACGIH_carcinogen", "ACGIH_Notations", "ACGIH_TLV_Basis", "ACGIHsmg", "ACGIHsppm", "ACGIHsppm", "CAN_AL_Carcinogen", "CAN_AL_Notation", "CAN_ALsmg", "CAN_ALsppm", "CAN_ALsppm", "CAN_ALsppm", "CAN_ONsmg", "CAN_ONsmg", "CAN_ONtmg", "CAN_ONtppm", "CAN_QCVECDmg - CANADA_QUEBEC VALEUR D""EXPOSITION DE COURTE DURÉE_mg", "CAN_QCVECDppm - CANADA_QUEBEC VALEUR D"EXPOSITION DE COURTE DURÉE_ppm", "CAN_QCVEMPmg - CANADA_QUEBEC VALEUR D"EXPOSITION MOYENNE PONDÉRÉE_mg", "CAN_QCVEMPppm - CANADA_QUEBEC VALEUR D"EXPOSITION MOYENNE PONDÉRÉE_ppm", "CANsppm", "CANtmg", "CANtmpm", "OSHA_SkinDesignation", "OSHA_Tables_Z1_Z2_Z3", "OSHACarcinogen - OSHA Carcinogen", "OSHAsmg", "OSHAsppm", "OSHAtmg", "OSHAtmg", "OSHAtppm"

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Density 9.60 lb/gal Specific Gravity 1.15

Clear Liquid **Appearance** Odor Description N/A Odor Threshold N/A N/A Melting/Freezing Point N/A Low Boiling Point 238.00 °C High Boiling Point N/A >149.00 °C Flash Point Vapor Pressure <1.00 mmHg Vapor Density N/A **Evaporation Rate** N/A

Evaporation Rate N/A
Upper Explosion Level N/A
Lower Explosion Level N/A

Water Solubility Insoluble in water

Coefficient Water/Oil N/A
Viscosity N/A

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable under normal storage and handling conditions.

Conditions To Avoid

Avoid heat, sparks, flame, high temperature and contact with incompatible materials.

Hazardous Reactions/Polymerization

Will not occur.

Incompatible Materials

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon.



CAS Number: 27138-31-4, 120-55-

3

Product Description: Thamesflex

705

SECTION 11) TOXICOLOGICAL INFORMATION

Acute Toxicity

May be harmful in contact with skin

May be harmful if swallowed

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is 3125 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is 3125 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

Aspiration Hazard

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation

Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available.

Mobility in Soil



CAS Number: 27138-31-4, 120-55-

,

Product Description: Thamesflex

705

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

	Transport Canada Information	U.S. DOT Information	IMDG Information	IATA Information
UN number:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Proper shipping name:	N/A	N/A	N/A	N/A
Hazard class:	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Packaging group:	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Hazardous substance (RQ):	No Data Available	No Data Available		
Marine Pollutant:	No Data Available	No Data Available	No Data Available	
Note / Special Provision:	No Data Available	No Data Available	vailable No Data Available No Data Avail	
Toxic-Inhalation Hazard:	No Data Available	No Data Available		

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0027138-31-4	PROPANOL, OXYBIS-, DIBENZOATE	65-85%	DSL, TSCA, AICS, CN_IECSC - Inventory of Existing Chemical Substances Produced or Imported in China, EU_EINECS - European_EC_Inventory_EINECS, EU_EC_Inventory - European_EC_Inventory, PH_PICCS - Philippines, The Philippine Inventory of Chemicals and Chemical Substances, KR_KECI - Korean Existing Chemicals Inventory
0000120-55-8	DIETHYLENE GLYCOL DIBENZOATE	10-30%	DSL, TSCA, AICS, CN_IECSC - Inventory of Existing Chemical Substances Produced or Imported in China, EU_EINECS - European_EC_Inventory_EINECS, EU_EC_Inventory - European_EC_Inventory, PH_PICCS - Philippines, The Philippine Inventory of Chemicals and Chemical Substances, KR_KECI - Korean Existing Chemicals Inventory

SECTION 16) OTHER INFORMATION

Thamesflex 705 Page 6 of 7



CAS Number: 27138-31-4, 120-55-

3

Product Description: Thamesflex

705

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

Version 1.0:

Revision Date: Jan 27, 2023

First Edition.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.