

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

CAS Number: 64742-52-5
Product Name: Calsol 810
Revision Date: Feb 21, 2018 **Date Printed:** Feb 21, 2018
Version: 1.0 **Supersedes Date:** N.A.
Manufacturer's Name: Thames River Chemical Corp.
Address: 5230 Harvester Road Burlington, ON, CA, L7L 4X4
Emergency Phone: CHEMTREC (800) 424-9300
Information Phone Number: 905-681-5353
Fax: 905-681-5377
Product/Recommended Uses: For laboratory or industrial use only.

SECTION 2) HAZARDS IDENTIFICATION

Classification

Aspiration Hazard - Category 1

Pictograms



Signal Word

Danger

Hazard Statements - Health

May be fatal if swallowed and enters airways

Precautionary Statements - General

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Precautionary Statements - Prevention

No precautionary statement available.

Precautionary Statements - Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local/national/international regulation. Waste management should be in full compliance with national, regional and local laws.

Physical Hazards Not Otherwise Classified

No Data Available

Health Hazards Not Otherwise Classified

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0064742-52-5	MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC	100%

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes or until medical aid is available. If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention. Wash contaminated clothing before re-use or discard.

Ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most Important Symptoms and Effects, Both Acute and Delayed

No Data Available

Indication of Any Immediate Medical Attention and Special Treatment Needed

No Data Available

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire: Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards in Case of Fire

Fire will produce irritating gases.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Move undamaged containers from immediate hazard area if it can be done safely.

Special Protective Actions

Wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Isolate hazard area and keep unauthorized personnel away. Stay uphill and/or upstream. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Ventilate closed spaces before entering.

Recommended Equipment

Wear chemical protective clothing.

Personal Precautions

Avoid breathing vapor or mist. Avoid contact with skin, eye or clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Dike far ahead of liquid spill for later disposal.

Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored All containers must be properly labelled.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits.

Storage Room Requirements

Store in dry, cool areas, out of direct sunlight and away from other sources of heat. Empty container retain residue and may be dangerous.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear indirect-vent, impact and splash resistant goggles when working with liquids

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	CANsmg	CANspmm	CANtmg	CANtppm	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA Carcinogen	OSHA Tables (Z1, Z2, Z3)	OSHA Skin designation	ACGIH STEL (mg/m3)
MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC							2000	500		1		

Chemical Name	ACGIH STEL (ppm)	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH TLV Basis	ACGIH Carcinogen	ACGIH Notations

MINERAL OIL,
PETROLEUM
DISTILLATES,
HYDROTREATED
(MILD) HEAVY
NAPHTHENIC

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	7.59 lb/gal
Specific Gravity	0.91
<hr/>	
Appearance	oily liquid
Odor Description	petroleum odour
Odor Threshold	N/A
pH	N/A
Melting/Freezing Point	0 °C
Low Boiling Point	207 °C
High Boiling Point	750 °C
Flash Point	167°C (open cup)
Vapor Pressure	<0.011 kPa
Vapor Density	N/A
Evaporation Rate	N/A
Upper Explosion Level	N/A
Lower Explosion Level	N/A
Water Solubility	Insoluble in cold water and hot water.
Coefficient Water/Oil	Log P(oct) = 3.9 - 6
Viscosity	kinematic (40°C): 18.7 cSt

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No Data Available

Stability

Stable under normal storage and handling conditions.

Conditions to Avoid

Avoid heat, sparks, flame, high temperature, freezing and contact with incompatible materials.

Hazardous Reactions/Polymerization

Hazardous polymerization will not occur.

Incompatible Materials

Strong bases, acids, oxidizing and reducing agents.

Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely Route of Exposure

Inhalation, ingestion, skin absorption

Acute Toxicity

Aspiration Hazard

May be fatal if swallowed and enters airways

Carcinogenicity

No Data Available

Germ Cell Mutagenicity

No Data Available

Reproductive Toxicity

No Data Available

Respiratory/Skin Sensitization

No Data Available

Serious Eye Damage/Irritation

No Data Available

Skin Corrosion/Irritation

No Data Available

Specific Target Organ Toxicity - Repeated Exposure

No Data Available

Specific Target Organ Toxicity - Single Exposure

No Data Available

0064742-52-5 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC

LD50 (Rodent - rat, Oral) : >5000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value.

LD50 (Rodent - rabbit, Administration onto the skin) : >2000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value.

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

No Data Available

Mobility in Soil

0064742-52-5 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC

Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

Bio-accumulative Potential

0064742-52-5 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC

Contains constituents with the potential to bioaccumulate.

Persistence and Degradability

No Data Available

Other Adverse Effects

No Data Available

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, provincial and local laws.

SECTION 14) TRANSPORT INFORMATION

Transport Canada Information

UN number: Not Regulated

Hazard class: N/A

Proper shipping name: N/A

Packaging group: N/A

U.S. DOT Information

UN number: Not Regulated

Hazard class: N/A

Proper shipping name: N/A

Packaging group: N/A

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0064742-52-5	MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC	100%	DSL,TSCA,EU_EC_Inventory - EC Inventory

SECTION 16) OTHER INFORMATION

Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CANsmg or CANspmm - Canadian Short Term Exposure Level in mg/L or in ppm; CANtmg or CANtppm - Canadian Time Weighted Average in mg/L or in ppm; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center(US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

Version 1.0:

Revision Date: Feb 21, 2018

First Edition.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.