

# SAFETY DATA SHEET

### SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

**CAS Number:** 527-07-1

Product Name: Sodium gluconate

 Revision Date:
 Mar 23, 2018
 Date Printed:
 Mar 23, 2018

 Version:
 1.1
 Supersedes Date:
 Jul 05, 2017

Manufacturer's Name: Thames River Chemical Corp.

Address: 5230 Harvester Road Burlington, ON, CA, L7L 4X4

Emergency Phone: CHEMTREC (800) 424-9300

**Information Phone Number:** 905-681-5353 **Fax:** 905-681-5377

Product/Recommended Uses: For laboratory or industrial use only.

### **SECTION 2) HAZARDS IDENTIFICATION**

#### Classification

Not classified

#### **Pictograms**

None

#### Signal Word

No signal word available.

#### **Precautionary Statements - General**

No precautionary statement available.

#### **Precautionary Statements - Prevention**

No precautionary statement available.

#### **Precautionary Statements - Response**

No precautionary statement available.

#### **Precautionary Statements - Storage**

No precautionary statement available.

### **Precautionary Statements - Disposal**

No precautionary statement available.

# **SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS**

CAS Chemical Name % By Weight

0000527-07-1 SODIUM GLUCONATE 100%

### **SECTION 4) FIRST-AID MEASURES**

### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

527-07-1 Page 1 of 6

#### **Eye Contact**

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes or until medical aid is available. If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open.

#### **Skin Contact**

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention. Wash contaminated clothing before re-use or discard.

#### Ingestion

Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Get medical advice/attention.

#### Most Important Symptoms and Effects, Both Acute and Delayed

No Data Available

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

No Data Available

### **SECTION 5) FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire: Water spray, fog or alcohol-resistant foam.

#### **Unsuitable Extinguishing Media**

Do not use straight stream of water.

#### Specific Hazards in Case of Fire

Fire will produce irritating gases.

#### **Fire-fighting Procedures**

Isolate immediate hazard area and keep unauthorized personnel out. Move undamaged containers from immediate hazard area if it can be done safely.

#### **Special Protective Actions**

Wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### **SECTION 6) ACCIDENTAL RELEASE MEASURES**

#### **Emergency Procedure**

Isolate hazard area and keep unauthorized personnel away. Stay uphill and/or upstream. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Ventilate closed spaces before entering.

### **Recommended Equipment**

Wear chemical protective clothing.

#### **Personal Precautions**

Avoid breathing vapor or mist. Avoid contact with skin, eye or clothing.

#### **Environmental Precautions**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Dike far ahead of liquid spill for later disposal.

#### Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

### **SECTION 7) HANDLING AND STORAGE**

527-07-1 Page 2 of 6

#### General

Highly water soluble; store in a dry environment. Ensure that containers are tightly sealed unless in use. If dust is formed in handling, install exhaust ventilation adequate to clear workplace air. Never cut, drill, weld or grind on or near this container.

Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored All containers must be properly labelled.

#### **Ventilation Requirements**

Use only with adequate ventilation to control air contaminants to their exposure limits.

#### **Storage Room Requirements**

Store in dry, cool areas, out of direct sunlight and away from other sources of heat. Empty container retain residue and may be dangerous.

### SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Eye protection

Wear indirect-vent, impact and splash resistant goggles when working with liquids

#### **Skin Protection**

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory Protection**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

#### **Appropriate Engineering Controls**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

| Chemical Name          | CANsmg | CANsppm | CANtmg | CANtppm | OSHA<br>STEL<br>(mg/m3) | OSHA<br>STEL<br>(ppm) | OSHA<br>TWA<br>(mg/m3) | OSHA<br>TWA<br>(ppm) | OSHA<br>Carcinogen | OSHA<br>Tables (Z1,<br>Z2, Z3) | OSHA<br>Skin<br>designation | ACGIH<br>STEL<br>(mg/m3) |
|------------------------|--------|---------|--------|---------|-------------------------|-----------------------|------------------------|----------------------|--------------------|--------------------------------|-----------------------------|--------------------------|
| No applicable chemical | -      | -       | -      | -       | -                       | -                     | -                      | -                    | -                  | -                              | -                           | -                        |

| Chemical Name          | ACGIH<br>STEL<br>(ppm) | ACGIH<br>TWA<br>(mg/m3) | ACGIH<br>TWA<br>(ppm) | ACGIH<br>TLV Basis | ACGIH<br>Carcinogen | ACGIH<br>Notations |
|------------------------|------------------------|-------------------------|-----------------------|--------------------|---------------------|--------------------|
| No applicable chemical | -                      | -                       | -                     | -                  | -                   | -                  |

### **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

### **Physical and Chemical Properties**

| Density<br>Specific Gravity | 15.02 lb/gal<br>1.80 |  |
|-----------------------------|----------------------|--|
| Appearance                  | Yellowish crystals   |  |
| Odor Description            | Odourless            |  |
| Odor Threshold              | N/A                  |  |
| рН                          | 3 (1% solution)      |  |

527-07-1 Page 3 of 6

Melting Point 265 °C

Low Boiling Point not known – calculated at 630°C

 High Boiling Point
 N/A

 Flash Point
 not known

 Vapor Pressure
 Nearly zero

 Vapor Density
 7.5 (air = 1)

Evaporation Rate Not known – not volatile

Upper Explosion Level N/A
Lower Explosion Level N/A
Water Solubility 590 g/l
Coefficient Water/Oil -5.99

Viscosity N/A - solid material

### **SECTION 10) STABILITY AND REACTIVITY**

#### Reactivity

No Data Available

# **Stability**

Stable under normal storage and handling conditions.

#### **Conditions to Avoid**

No data available.

### **Hazardous Reactions/Polymerization**

Hazardous polymerization will not occur.

### **Incompatible Materials**

Strong-oxidizing agents.

### **Hazardous Decomposition Products**

No Data Available

# **SECTION 11) TOXICOLOGICAL INFORMATION**

### Likely Route of Exposure

Inhalation, ingestion, skin absorption

### **Acute Toxicity**

### **Aspiration Hazard**

No Data Available

# Carcinogenicity

No Data Available

### **Germ Cell Mutagenicity**

No Data Available

### **Reproductive Toxicity**

No Data Available

### Respiratory/Skin Sensitization

No Data Available

# Serious Eye Damage/Irritation

No Data Available

#### Skin Corrosion/Irritation

No Data Available

527-07-1 Page 4 of 6

### **Specific Target Organ Toxicity - Repeated Exposure**

No Data Available

### **Specific Target Organ Toxicity - Single Exposure**

No Data Available

### **SECTION 12) ECOLOGICAL INFORMATION**

#### **Toxicity**

No Data Available

#### **Mobility in Soil**

No Data Available

#### **Bio-accumulative Potential**

No Data Available

### Persistence and Degradability

No Data Available

#### Other Adverse Effects

No Data Available

## **SECTION 13) DISPOSAL CONSIDERATIONS**

### **Waste Disposal**

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, provincial and local laws.

# **SECTION 14) TRANSPORT INFORMATION**

# **Transport Canada Information**

UN number: Not Regulated Proper shipping name: N/A

Hazard class: N/A
Packaging group: N/A

### **U.S. DOT Information**

UN number: Not Regulated Proper shipping name: N/A

Hazard class: N/A
Packaging group: N/A

### **SECTION 15) REGULATORY INFORMATION**

527-07-1 Page 5 of 6

| CAS          | Chemical Name    | % By Weight | Regulation List |
|--------------|------------------|-------------|-----------------|
| 0000527-07-1 | SODIUM GLUCONATE | 100%        | DSL,TSCA        |

# **SECTION 16) OTHER INFORMATION**

#### **Glossary**

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CANsmg or CANsppm - Canadian Short Term Exposure Level in mg/L or in ppm; CANtmg or CANtppm - Canadian Time Weighted Average in mg/L or in ppm; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center(US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

#### Version 1.1:

Revision Date: Mar 23, 2018

#### **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

527-07-1 Page 6 of 6