

SAFETY DATA SHEET

CAS Number: 34398-01-1 (100%) Product Description: Thamesurf 1-5

	SECTION 1) CHEMICA	L PRODUCT AND SUPPLIE	R'S IDENTIFICATION	
CAS Number:	34398-01-1			
Product Name:	Thamesurf 1-5			
Revision Date:	May 16, 2021	Date Printed:	Jun 16, 2021	
Version:	1.0	Supersedes Date:	N.A.	
Manufacturer's Name:	Thames River Chemical Corp).		
Address:	5230 Harvester Road Burlingt	on, ON, CA, L7L 4X4		
Emergency Phone:	CHEMTREC (800) 424-9300			
Information Phone Numb	oer: 905-681-5353			
Fax:	905-681-5377			
Product/Pecommended	leas: For laboratory or industrial	use only		

Product/Recommended Uses: For laboratory or industrial use only.

SECTION 2) HAZARDS IDENTIFICATION

Classification

Acute toxicity Oral - Category 4

Serious Eye Damage - Category 1

Pictograms



Signal Word

Danger

Hazard Statements - Health

Harmful if swallowed

Causes serious eye damage

Precautionary Statements - General

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Precautionary Statements - Prevention

Wash/Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

IF SWALLOWED: Call a POISON CENTER or doctor, if you feel unwell.

Rinse mouth.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.



Precautionary Statements - Storage

No precautionary statement available.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local/national/international regulation. Waste management should be in full compliance with national, regional and local laws.

Physical Hazards Not Otherwise Classified

No data available.

Health Hazards Not Otherwise Classified

No data available.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0034398-01-1	Poly(oxy-1,2-ethanediyl), .alphaundecylomega hydroxy-	100%

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes or until medical aid is available. Seek medical attention.

Skin Contact

Seek immediately medical advice.

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed. Wash contaminated clothing before re-use or discard.

Ingestion

Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Where medical attention is not immediately available or where the patient is more than 15

minutes from a hospital or unless instructed otherwise:

INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms/injuries after eye contact: Symptoms include stinging, watering, redness, and swelling. Symptoms/injuries after ingestion: Swallowing of this material will result in serious health hazard.

Indication of Any Immediate Medical Attention and Special Treatment Needed

Treat symptomatically

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media



Use extinguishing media suitable for surrounding fire.

Water spray or carbon dioxide

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards in Case of Fire

Thermal decomposition may lead to release of irritating or toxic gases/vapors.

Non-flammable.

Fire will produce irritating gases.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Move undamaged containers from immediate hazard area if it can be done safely.

Special Protective Actions

Wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Isolate hazard area and keep unauthorized personnel away. Stay uphill and/or upstream. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Ventilate closed spaces before entering.

Recommended Equipment

Wear chemical protective clothing.

Personal Precautions

Avoid breathing vapor or mist. Avoid contact with skin, eye or clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Dike far ahead of liquid spill for later disposal.

Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Do not get in eyes, on skin or on clothing. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits.

Storage Room Requirements

Storage temperature: 50 - 100 °F

Store in dry, cool areas, out of direct sunlight and away from other sources of heat. Store in original containers. Keep containers securely sealed.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION



SAFETY DATA SHEET

Eye protection

Wear indirect-vent, impact and splash resistant goggles when working with liquids

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	CANsmg	CANsppm	CANtmg	CANtppm	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)
No applicable chemical	-	-	-	-	-	-	-	-

Chemical	OSHA	OSHA Tables	OSHA Skin designation	ACGIH STEL	ACGIH STEL	ACGIH TWA	ACGIH TWA	ACGIH
Name	Carcinogen	(Z1, Z2, Z3)		(mg/m3)	(ppm)	(mg/m3)	(ppm)	TLV Basis
No applicable chemical	-	-	-	-	-	-	-	-

Chemical	ACGIH	ACGIH
Name	Carcinogen	Notations
No applicable chemical	-	-

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density Specific Gravity	8.35 lb/gal 1.00
Appearance	Clear Liquid to slightly turbid
Odor Description	Mild
Odor Threshold	N/A
рН	no data availible
Melting/Freezing Point	no data availible
Low Boiling Point	no data availible
High Boiling Point	N/A
Flash Point	150 °C
Vapor Pressure	no data availible
Vapor Density	pas de données disponibles
Evaporation Rate	no data availible
Upper Explosion Level	N/A



CAS Number: 34398-01-1 (100%) Product Description: Thamesurf 1-5

Lower Explosion Level Water Solubility Coefficient Water/Oil Viscosity N/A 9.4 g/l no data availible 21 cSt (37 C)

SECTION 10) STABILITY AND REACTIVITY

Possibility of hazardous reactions

No data available.

Reactivity

No data available.

Stability

Stable under normal storage and handling conditions.

Conditions to Avoid

Direct sunlight. Extremely high or low temperatures

Hazardous Reactions/Polymerization

Hazardous polymerization will not occur.

Incompatible Materials

Materials reactive with hydroxyl compounds. Strong acids

Hazardous Decomposition Products

Thermal decomposition generates : Carbon oxides. Aldehydes. Flammable hydrocarbon fragments.

SECTION 11) TOXICOLOGICAL INFORMATION

Acute Toxicity

LD50 Oral (Rat):1,000 - 2,000 mg/kg

Harmful if swallowed

Aspiration Hazard

No data available.

Carcinogenicity

No data available.

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Respiratory/Skin Sensitization

No data available.

Serious Eye Damage/Irritation

Causes serious eye damage

Skin Corrosion/Irritation

Causes mild skin irritation



Specific Target Organ Toxicity - Repeated Exposure

No data available.

Specific Target Organ Toxicity - Single Exposure

No data available.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

CAS: 34398-01-1 LC50 (96h) fish:1-10 mg/l EC50 (48h) Daphnia: 1-10 mg/l EC50 (96h) Algae: 1-10 mg/l

Mobility in Soil

No data available.

Bioaccumulative Potential

No data available.

Persistence and Degradability

Readily biodegradable as OECD (degrades greater than 60-70% within 10 day window over 28 days)

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Waste Disposal

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, provincial and local laws.

SECTION 14) TRANSPORT INFORMATION				
	SECTION 14) TR			
	Transport Canada Information	U.S. DOT Information		
UN number:	Not Regulated	Not Regulated		
Proper shipping name:	N/A	N/A		
Hazard class:	Not Applicable	Not Applicable		
Packaging group:	Not Applicable	Not Applicable		
Hazardous		No Data Available		

substance (RQ):



SAFETY DATA SHEET

Marine Pollutant:	No Data Available	No Data Available
Note / Special Provision:	No Data Available	No Data Available
Toxic-Inhalation Hazard:		No Data Available
Transport in bulk (according to Annex II of MARPOL 73/78):	No Data Available	

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0034398-01-1	Poly(oxy-1,2-ethanediyl), .alpha undecylomegahydroxy-	100%	DSL,TSCA,EU_EC_Inventory - European_EC_Inventory

SECTION 16) OTHER INFORMATION

Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CANsmg or CANsppm - Canadian Short Term Exposure Level in mg/L or in ppm; CANtmg or CANtppm - Canadian Time Weighted Average in mg/L or in ppm; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center(US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

Version 1.0:

Revision Date: Jun 16, 2021 Version 1.0

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.